

A Quality Product from Hawkeye Industries Inc.



Duratec® Polyurethane Wood Sealer

A low viscosity penetrating polyurethane sealer that anchors lacquers, polyesters, vinyl esters, polyurethane and most epoxies to wood substrates. This exceptional two-component sealer adheres to difficult-to-bond-to woods, such as teak, mahogany, ebony, rosewood, etc.

Usage

For sealing wood substrates in preparation for topcoating with clear and pigmented coatings.

Features

You'll get exceptional adhesion to difficult-to-bond-to wood and wood veneer substrates with Duratec Polyurethane Wood Sealer.

Here's why you should choose Duratec Polyurethane Wood Sealer—

Easy to apply—apply with a brush or sprayer.

Rapid curing—able to be topcoated within 90-120 minutes.

Deep penetration—covers and seals oily woods and veneers.

Packaging—packaged for correct mixing proportions.

Duratec Polyurethane Wood Sealer

5604-002

5604-002B (Catalyst)



Hawkeye Industries Inc.

P O Box 415 Bloomington, CA 92316

Tel 909-546-1160; Toll Free 800-977-0060; Fax: 909-546-1161

Email hawkeyesales@hawkeyeind.com Web www.duratec1.com

Liability/warranty statement: Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.

Duratec is a registered trademark of Dura Technologies Inc.



Product No. 5604-002

Data Sheet
Continued

Duratec Polyurethane Wood Sealer

Pg. 2

Product Properties

All time calculations are based on temperatures of 77° F, 25°C

Pot Life

60 min.

Viscosity

Measured with #2 Zahn cup

18-24 sec.

Mix Ratio

66 Part A to 33 Part B

Weight per Gallon

8.4 lbs, 3.81 kg

Revised 3-16-16



Hawkeye Industries Inc.

P O Box 415 Bloomington, CA 92316

Tel 909-546-1160; Toll Free 800-977-0060; Fax: 909-546-1161

Email hawkeyesales@hawkeyeind.com Web www.duratec1.com

Liability/warranty statement: Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.

Duratec is a registered trademark of Dura Technologies Inc.