



DURATEC COATING VOC

702-003

BLACK SURFACE PRIMER

The Composites Fabricators Association in association with the EPA conducted a study of styrene emissions from open mold composite manufacturing. Styrene monomer is a volatile liquid that will react to form a non-volatile copolymer with unsaturated polyester resins. The value to determine is thus the amount of material lost prior to the completion of the reaction. The data gathered in this study is the actual measurement of emissions based on the percent styrene in the coating and the application method chosen. It was shown that the non-atomizing applications (such as brushing or roll coating) emit much less than the atomizing application (spraying). Using the data from this study, a Unified Emissions Factor (UEF) table was prepared.

Dura Technologies, Inc. considers this to be the best available science for calculating the emissions of coatings containing styrene monomer. We will therefore report three distinct VOC numbers. The VOC reported in section III of the MSDS is based on 100% evaporation of the styrene. This attachment will report the VOC calculated using the UEF factors for atomized application and non-atomized application.

ATOMIZED APPLICATION

| | | |
|---------------------------|-----------------------|------------------|
| COATING VOC: 2.25 | LB/GAL (269.7 | GR/LITER) |
| MATERIAL VOC: 2.25 | LB/GAL (269.7 | GR/LITER) |

NON-ATOMIZED APPLICATION

| | | |
|---------------------------|---------------------|------------------|
| COATING VOC: 1.73 | LB/GAL (207 | GR/LITER) |
| MATERIAL VOC: 1.73 | LB/GAL (207 | GR/LITER) |

For some applications, this product may not be compliant if applied using atomizing techniques. Please consult the AQMD rule that applies to you operation and determine which application method will comply.

BLACK SURFACE PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : BLACK SURFACE PRIMER
CAS No : mixture
Product code : 702-003
Formula : na

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : COATING

1.3. Details of the supplier of the safety data sheet

Dura Technologies, Inc.
2720 South Willow Avenue #A
Bloomington, CA 92316

909.877.8477
ChemTrec US: 800.424.9300
ChemTrec Int: +1 70 3527 3887

1.4. Emergency telephone number

Emergency number : ChemTrec US: 800.424.9300 Int: +1 70 3527 3887
CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 3 H226
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Carc. Not classified

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor
H315 - Causes skin irritation
H319 - Causes serious eye irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P264 - Wash exposed areas. thoroughly after handling
P280 - Wear eye protection, protective clothing, protective gloves
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P321 - Specific treatment (see none listed. on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use carbon dioxide (CO2), dry chemical powder, foam to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool

BLACK SURFACE PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container to in accordance with local, state, and federal regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

| Name | Product identifier | % | Classification (GHS-US) |
|-----------------------------|-----------------------|--------|--|
| Proprietary Resin | (CAS No) TRADE SECRET | <= 35 | Not classified |
| talc | (CAS No) 14807-96-6 | <= 33 | Not classified |
| styrene, inhibited | (CAS No) 100-42-5 | <= 21 | Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 |
| cobalt(II) 2-ethylhexanoate | (CAS No) 136-52-7 | <= 0.5 | Carc. 2, H351 |

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: wash thoroughly for five minutes. seek medical attention. Get medical advice/attention. Specific treatment (see seek medical attention. on this label).
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: SEEK IMMEDIATE MEDICAL ATTENTION. Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause genetic defects (avoid skin contact and inhalation.). May cause cancer (avoid skin contact and inhalation.).
- Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor.
- Explosion hazard : May form flammable/explosive vapor-air mixture.
- Reactivity : No reactivity hazard other than the effects described in sub-sections below.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

BLACK SURFACE PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Protective goggles. Protective clothing.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing DUST, FUMES, MIST, OR VAPORS. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so.

Hygiene measures : Wash HANDS thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : HEAT SPARKS OR OPEN FLAMES. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| styrene, inhibited (100-42-5) | | |
|-------------------------------|------------------|--------|
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 40 ppm |

| talc (14807-96-6) | | |
|-------------------|--------------------------------|---------------------|
| USA ACGIH | ACGIH TWA (mg/m ³) | 2 mg/m ³ |

8.2. Exposure controls

Appropriate engineering controls : Ensure exposure is below occupational exposure limits (where available).

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

BLACK SURFACE PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--------------------------|---|
| Eye protection | : Chemical goggles or safety glasses. |
| Skin and body protection | : Wear suitable protective clothing. |
| Respiratory protection | : Wear approved mask. |
| Other information | : When using, do not eat, drink or smoke. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---------------------|
| Physical state | : Liquid |
| Color | : Black. |
| Odor | : characteristic. |
| Odor threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : ≥ 64.4 °C |
| Flash point | : ≥ -6.67 °C |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : ≥ 1.3 |
| Solubility | : No data available |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Polymerization can result in formation of solid deposits, even in vapour space. Not established. Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|----------------|------------------|
| Acute toxicity | : Not classified |
|----------------|------------------|

BLACK SURFACE PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| BLACK SURFACE PRIMER (f)mixture | |
|--|---------------|
| ATE CLP (dust, mist) | 1.500 mg/l/4h |

| styrene, inhibited (100-42-5) | |
|--------------------------------------|---|
| LD50 oral rat | 5000 mg/kg (>6000 mg/kg bodyweight; Rat; Rat) |
| LD50 dermal rat | 2820 mg/kg (>2000 mg/kg bodyweight; Rat; Rat; Experimental value) |
| LD50 dermal rabbit | 5010 mg/kg (Rabbit) |
| LC50 inhalation rat (mg/l) | 12 mg/l/4h (Rat) |
| LC50 inhalation rat (ppm) | 2770 ppm/4h (Rat) |
| ATE CLP (oral) | 5000.000 mg/kg body weight |
| ATE CLP (dermal) | 2820.000 mg/kg body weight |
| ATE CLP (gases) | 2770.000 ppmV/4h |
| ATE CLP (vapors) | 12.000 mg/l/4h |
| ATE CLP (dust, mist) | 12.000 mg/l/4h |

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified.

| styrene, inhibited (100-42-5) | |
|--------------------------------------|--------------------------------------|
| IARC group | 2B - Possibly Carcinogenic to Humans |

| talc (14807-96-6) | |
|--------------------------|----------------------|
| IARC group | 3 - Not classifiable |

| cobalt(II) 2-ethylhexanoate (136-52-7) | |
|---|--------------------------------------|
| IARC group | 2B - Possibly Carcinogenic to Humans |

Reproductive toxicity : Not classified
Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified
Based on available data, the classification criteria are not met
Aspiration hazard : Not classified
Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms : Harmful if inhaled.
Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
Symptoms/injuries after skin contact : Causes skin irritation.
Symptoms/injuries after eye contact : Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

| styrene, inhibited (100-42-5) | |
|---|---|
| LC50 fish 1 | 25 mg/l (96 h; Lepomis macrochirus) |
| LC50 other aquatic organisms 1 | 10 - 100 mg/l (96 h) |
| EC50 Daphnia 1 | 23 mg/l (48 h; Daphnia magna; LOCOMOTOR EFFECT) |
| LC50 fish 2 | 32 mg/l (96 h; Pimephales promelas) |
| EC50 Daphnia 2 | 27 mg/l (24 h; Daphnia magna) |
| TLM fish 1 | 25.1 mg/l (96 h; Lepomis macrochirus; SOFT WATER) |
| TLM fish 2 | 46.4 mg/l (96 h; Pimephales promelas; SOFT WATER) |
| TLM other aquatic organisms 1 | 10 - 100,96 h |
| Threshold limit other aquatic organisms 1 | 10 - 100,96 h; Pseudomonas putida |
| Threshold limit other aquatic organisms 2 | 72 mg/l |

BLACK SURFACE PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| styrene, inhibited (100-42-5) | |
|--------------------------------------|---|
| Threshold limit algae 1 | > 200 mg/l (192 h; Scenedesmus quadricauda; INHIBITORY) |
| Threshold limit algae 2 | 67 mg/l (Microcystis aeruginosa; INHIBITORY) |

| talc (14807-96-6) | |
|--------------------------|--|
| LC50 fish 1 | > 100 g/l (24 h; Brachydanio rerio; INTERMITTENT FLOW) |

12.2. Persistence and degradability

| BLACK SURFACE PRIMER (mixture) | |
|---------------------------------------|------------------|
| Persistence and degradability | Not established. |

| styrene, inhibited (100-42-5) | |
|--------------------------------------|--|
| Persistence and degradability | Readily biodegradable in water. Not readily biodegradable in water. Forming sediments in water. Non degradable in the soil. Adsorbs into the soil. Photodegradation in the air. Not established. |
| Chemical oxygen demand (COD) | 2.80 g O ₂ /g substance |
| ThOD | 3.07 g O ₂ /g substance |
| BOD (% of ThOD) | 0.42 % ThOD |

| Proprietary Resin (TRADE SECRET) | |
|---|------------------|
| Persistence and degradability | Not established. |

| talc (14807-96-6) | |
|---------------------------------|-----------------------------------|
| Persistence and degradability | Biodegradability: not applicable. |
| Biochemical oxygen demand (BOD) | Not applicable |
| Chemical oxygen demand (COD) | Not applicable |
| ThOD | Not applicable |
| BOD (% of ThOD) | Not applicable |

| cobalt(II) 2-ethylhexanoate (136-52-7) | |
|---|---|
| Persistence and degradability | Biodegradability in water: no data available. |

12.3. Bioaccumulative potential

| BLACK SURFACE PRIMER (mixture) | |
|---------------------------------------|------------------|
| Bioaccumulative potential | Not established. |

| styrene, inhibited (100-42-5) | |
|--------------------------------------|---|
| BCF fish 1 | 12 - 77 (QSAR) |
| BCF fish 2 | 35.5 (Carassius auratus) |
| Log Pow | 2.95 - 3.16 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). Not established. |

| Proprietary Resin (TRADE SECRET) | |
|---|------------------|
| Bioaccumulative potential | Not established. |

| cobalt(II) 2-ethylhexanoate (136-52-7) | |
|---|------------------------------------|
| Bioaccumulative potential | No bioaccumulation data available. |

12.4. Mobility in soil

| styrene, inhibited (100-42-5) | |
|--------------------------------------|-------------------|
| Surface tension | 0.032 N/m (19 °C) |

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to approved disposal site.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

BLACK SURFACE PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with DOT

UN-No.(DOT) : UN1263
DOT Proper Shipping Name : PAINT
Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

Additional information

Other information : No supplementary information available.

ADR

Transport document description : UN 1263, 3, II, (D/E)
Packing group (ADR) : II
Class (ADR) : 3 - Flammable liquid
Hazard identification number (Kemler No.) : 33
Classification code (ADR) : F1
Danger labels (ADR) : 3 - Flammable liquids



Orange plates :



Tunnel restriction code : D/E
LQ : 5L
Excepted quantities (ADR) : E2

Transport by sea

UN-No. (IMDG) : 1263
Proper Shipping Name (IMDG) : paint
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No.(IATA) : 1263
Proper Shipping Name (IATA) : paint
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

styrene, inhibited (100-42-5)

| | |
|--|---------|
| RQ (Reportable quantity, section 304 of EPA's List of Lists) : | 1000 lb |
|--|---------|

BLACK SURFACE PRIMER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

styrene, inhibited (100-42-5)

| | |
|-------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Reactive hazard Fire hazard Delayed (chronic) health hazard |
|-------------------------------------|--|

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

| | |
|-------------------------------------|------|
| Flam. Liq. 2 | H225 |
| Acute Tox. 4 (Inhalation:dust,mist) | H332 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2 | H319 |
| Muta. 1B | H340 |
| Carc. 1B | H350 |

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

Carc.Cat.2; R45
Muta.Cat.2; R46
F; R11
Xn; R20
Xi; R36/38

Full text of R-phrases: see section 16

15.2.2. National regulations

styrene, inhibited (100-42-5)

Listed on EPA's Hazardous Air Pollutants (HAPS)

15.3. US State regulations

styrene, inhibited (100-42-5)

| | | | | |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
|---|---|---|---|-----------------------------------|

styrene, inhibited (100-42-5)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

BLACK SURFACE PRIMER


Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases: see section 16:

| | |
|----------------------------------|---|
| Acute Tox. 4 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 4 |
| Carc. 2 | Carcinogenicity Category 2 |
| Carc. Not classified | Carcinogenicity Not classified |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Flam. Liq. 3 | Flammable liquids Category 3 |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| H226 | Flammable liquid and vapor |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H351 | Suspected of causing cancer |

- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.
- NFPA reactivity : 2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive mixtures with water.



HMIS III Rating

- Health : 2 Moderate Hazard - Temporary or minor injury may occur
- Flammability : 3 Serious Hazard
- Physical : 1 Slight Hazard
- Personal Protection : H

SDS US (GHS HazCom 2012)

To the best of our knowledge this SDS is accurate. The the extent allowed by law, this statement is made in lieu of an other warranties, expressed or implied including but not limited to any implied warranty of merchantability or fitness for a particular purpose and is in lieu of any other obligations or liability on the part of Dura Technologies, Inc.