

TECHNICAL DATA SHEET

FLASH TAPE 1**Pressure-Sensitive Silicone Adhesive Polyester Tape****DESCRIPTION:**

Flash Tape 1 is a multi-purpose .001" thick, translucent polyester film coated with a .0015" thick fully cured silicone adhesive.

APPLICATION:

Flash Tape 1 is designed for all phases of masking operations where no residue can be tolerated. **Flash Tape 1** is perfect for holding release films and fabrics, bleeders and breathers, metal and composite details in place during pre-fit and pre-bond operations. **Flash Tape 1** will release cleanly without leaving residue on metals and composite details. It is highly recommended for long term temperature exposures over 350°F.

TECHNICAL DATA:

	TYPICAL VALUES
Color	Blue Translucent
Backing	Polyester
Thickness	Film .001" (.025mm); Adhesive .0015" (.037mm)
Adhesive	Silicone, fully cured
Tensile, lb./in. width	25 lb./in. width (4.3 kg./cm.)
Adhesion to Steel, oz./in. width	35 oz./in. width (.39 kg./cm.)
Elongation	100% Minimum
Use Temperature	400°F max. (204°C max.)

The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.

AVAILABILITY:

Standard Roll Sizes: 1" x 72 yards
2" x 72 yards

Custom sizes available upon request (minimums may apply)

Technical information furnished is based on laboratory findings and is believed to be correct. No warranties of any kind are made except that the materials are of standard quality. All risk and liabilities arising from handling, storage and use of product, as well as compliance with applicable legal restrictions rest with the buyer. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.