



Hawkeye Industries Inc.

Duratec® & Aqua Buff®
Products Marketed Worldwide

Duratec Thinner

Duratec Thinner LAC-3 is the perfect solvent for the Duratec product range.

- Matches the original solvent cut, assuring complete compatibility.
- Efficient: little thinner is required to cut the viscosity for good spraying. Allows for reduced air pressure reducing overspray and eliminating orange peel.
 - No HAPS.
 - Fast Evaporating: does not extend the cure time of the sprayed-out Duratec.
 - Improves leveling: reduce or eliminate orange peel.
 - Will not create the rough surface associated with dry spray.
 - “Dry”...low water content to avoid fogging or dulling topcoats.

How to use:

Mix the Duratec.

1. Add Gel-X (if necessary) and catalyst.
2. If the viscosity is too high for spraying, add one ounce of Duratec Thinner per quart of Duratec. Mix, and evaluate the viscosity. Usually, no more than three ounces of Duratec Thinner are necessary per quart of Duratec.
3. Spray the Duratec.

Visit www.duratec1.com for more application information.



DURATEC

SURFACING TECHNOLOGY ISO 9001: 2008

P. O. Box 415, Bloomington, CA 92316 • (USA) 800-977-0060 • (Outside USA) 909-546-1160
Fax: 909-546-1161 | Email: hawkeyesales@hawkeyeind.com | www.duratec1.com