



**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product form : Mixture  
Trade name : DURATEC THINNER  
CAS No : mixture  
Product code : 39LAC-3  
Formula : na

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : PAINT THINNER

**1.3. Details of the supplier of the safety data sheet**

Dura Technologies, Inc.  
2720 South Willow Avenue #A  
Bloomington, CA 92316

909.877.8477  
ChemTrec US: 800.424.9300  
ChemTrec Int: +1 70 3527 3887

**1.4. Emergency telephone number**

Emergency number : ChemTrec US: 800.424.9300 Int: +1 70 3527 3887  
CHEMTREC: 1-800-424-9300

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**GHS-US classification**

Flam. Liq. 2 H225  
Acute Tox. Not classified (Oral)  
Skin Irrit. Not classified  
Eye Irrit. 2A H319  
Muta. 1B H340  
Carc. 1B H350  
STOT SE 3 H336  
STOT SE 3 H335  
Asp. Tox. 1 H304

**2.2. Label elements**

**GHS-US labeling**

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H340 - May cause genetic defects  
H350 - May cause cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat; hot surfaces; open flames. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical; lighting; ventilating equipment  
P242 - Use only non-sparking tools

# DURATEC THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing dust, fume, mist, spray, vapors  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear eye protection; protective clothing  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - IF exposed or concerned: Get medical advice/attention  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell  
P331 - If swallowed, do NOT induce vomiting  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), dry chemical powder, foam to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to in accordance with local, state, and national regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Solvent Naptha Petroleum Aliphatic	(CAS No) Proprietary	<= 39	Not classified
methyl ethyl ketone	(CAS No) 78-93-3	<= 22	Flam. Liq. 2, H225 STOT SE 3, H336
n-butyl acetate	(CAS No) 123-86-4	<= 20	Flam. Liq. 3, H226 STOT SE 3, H336
isobutyl acetate	(CAS No) 110-19-0	<= 11	Flam. Liq. 2, H225
2-propanol	(CAS No) 67-63-0	<= 10	Flam. Liq. 2, H225 STOT SE 3, H336

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: wash thoroughly for five minutes. seek medical attention. Get medical advice/attention. Specific treatment (see seek medical attention. on this label). Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: SEEK IMMEDIATE MEDICAL ATTENTION. Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause genetic defects (avoid skin contact and inhalation.). May cause cancer (avoid skin contact and inhalation.).

Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

# DURATEC THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.  
Explosion hazard : May form flammable/explosive vapor-air mixture.  
Reactivity : No reactivity hazard other than the effects described in sub-sections below.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

#### 6.1.1. For non-emergency personnel

Protective equipment : Gloves. Protective goggles. Protective clothing.  
Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.  
Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers.  
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.  
Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing DUST, FUMES, MIST, OR VAPORS. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools.  
Hygiene measures : Wash HANDS thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/... equipment.  
Storage conditions : Keep in fireproof place. Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

# DURATEC THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

methyl ethyl ketone (78-93-3)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	200 ppm

n-butyl acetate (123-86-4)		
USA ACGIH	ACGIH TWA (ppm)	150 ppm
USA ACGIH	ACGIH STEL (ppm)	200 ppm

isobutyl acetate (110-19-0)		
USA ACGIH	ACGIH TWA (ppm)	150 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm

2-propanol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	200 ppm

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits (where available).
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.
Other information	: Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: clear.
Odor	: characteristic.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: < °C
Freezing point	: No data available
Boiling point	: >= 79.4 °C
Flash point	: >= -6.11 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.8
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available

# DURATEC THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

Polymerization can result in formation of solid deposits, even in vapour space. Highly flammable liquid and vapor. Not established. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified.

methyl ethyl ketone (78-93-3)	
LD50 oral rat	2737 mg/kg (Rat; Equivalent or similar to OECD 423; Read-across; 2054 mg/kg; Rat; Equivalent or similar to OECD 423; Read-across; 2328 mg/kg; Rat)
LD50 dermal rabbit	6480 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; >10; Rabbit)
LC50 inhalation rat (mg/l)	34 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	11300 ppm/4h (Rat; Literature study)
ATE CLP (oral)	2737.000 mg/kg body weight
ATE CLP (dermal)	6480.000 mg/kg body weight
ATE CLP (gases)	11300.000 ppmV/4h
ATE CLP (vapors)	34.000 mg/l/4h
ATE CLP (dust, mist)	34.000 mg/l/4h

n-butyl acetate (123-86-4)	
LD50 oral rat	10770 mg/kg (Rat)
LD50 dermal rabbit	> 17600 mg/kg (Rabbit)
ATE CLP (oral)	10770.000 mg/kg body weight

isobutyl acetate (110-19-0)	
LD50 oral rat	13400 mg/kg (Rat)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit)
ATE CLP (oral)	13400.000 mg/kg body weight

2-propanol (67-63-0)	
LD50 oral rat	5045 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; 5840 mg/kg bodyweight; Rat)
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)
ATE CLP (oral)	5045.000 mg/kg body weight
ATE CLP (dermal)	12870.000 mg/kg body weight

# DURATEC THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>2-propanol (67-63-0)</b>	
ATE CLP (vapors)	73.000 mg/l/4h
ATE CLP (dust, mist)	73.000 mg/l/4h
Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

<b>2-propanol (67-63-0)</b>	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness. May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: May be fatal if swallowed and enters airways. Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Harmful if inhaled. Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>methyl ethyl ketone (78-93-3)</b>	
LC50 fish 1	1690 mg/l (96 h; Lepomis macrochirus; Lethal)
EC50 Daphnia 1	308 mg/l (48 h; Daphnia magna; Locomotor effect)
LC50 fish 2	2990 mg/l (96 h; Pimephales promelas)
TLM fish 1	5600 mg/l (96 h; Gambusia affinis)
TLM fish 2	1690 mg/l (96 h; Lepomis macrochirus)
TLM other aquatic organisms 1	> 1000 ppm (96 h)
Threshold limit algae 1	110 mg/l (168 h; Microcystis aeruginosa)
Threshold limit algae 2	4300 mg/l (192 h; Scenedesmus quadricauda)

<b>n-butyl acetate (123-86-4)</b>	
LC50 fish 1	18 mg/l (96 h; Pimephales promelas)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	10 - 100 mg/l (48 h; Daphnia magna; Static system)
EC50 other aquatic organisms 1	320 mg/l (96 h; Algae)
LC50 fish 2	62 mg/l (96 h; Brachydanio rerio)
EC50 Daphnia 2	24 - 205 mg/l (24 h; Daphnia magna)
TLM fish 1	10 - 100,96 h; Pisces
Threshold limit other aquatic organisms 1	10 - 100,96 h
Threshold limit algae 1	21 mg/l (168 h; Scenedesmus quadricauda; GROWTH RATE)
Threshold limit algae 2	280 mg/l (192 h; Microcystis aeruginosa; GROWTH RATE)

<b>isobutyl acetate (110-19-0)</b>	
LC50 fish 1	100 mg/l (96 h; Lepomis macrochirus)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	44 mg/l (48 h; Daphnia magna; Nocivity test)
LC50 fish 2	101 mg/l (48 h; Leuciscus idus)

# DURATEC THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>isobutyl acetate (110-19-0)</b>	
EC50 Daphnia 2	146 - 192 mg/l (Daphnia magna)
TLM fish 1	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	10 - 100,96 h; Protozoa
Threshold limit other aquatic organisms 2	411 mg/l (72 h)
Threshold limit algae 1	205 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	80 mg/l (192 h; Scenedesmus quadricauda)

<b>2-propanol (67-63-0)</b>	
LC50 fish 1	4200 mg/l (96 h; Rasbora heteromorpha; Flow-through system)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna)
LC50 fish 2	9640 mg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 2	13299 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 1000 mg/l (72 h; Scenedesmus subspicatus; Growth rate)
Threshold limit algae 2	1800 mg/l (72 h; Algae; Cell numbers)

### 12.2. Persistence and degradability

<b>DURATEC THINNER (mixture)</b>	
Persistence and degradability	Not established.

<b>methyl ethyl ketone (78-93-3)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Not established.
Biochemical oxygen demand (BOD)	1.92 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.31 g O <sub>2</sub> /g substance
ThOD	2.44 g O <sub>2</sub> /g substance
BOD (% of ThOD)	> % ThOD (5 day(s)) > 0.5

<b>n-butyl acetate (123-86-4)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Not established.
Biochemical oxygen demand (BOD)	0.15 - 0.5 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.32 g O <sub>2</sub> /g substance
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	46 % ThOD

<b>isobutyl acetate (110-19-0)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photolysis in the air. Not established.
ThOD	2.2 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.60 % ThOD

<b>2-propanol (67-63-0)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established.
Biochemical oxygen demand (BOD)	1.19 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.23 g O <sub>2</sub> /g substance
ThOD	2.40 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.49 % ThOD

<b>Solvent Naptha Petroleum Aliphatic (Proprietary)</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative potential

<b>DURATEC THINNER (mixture)</b>	
Bioaccumulative potential	Not established.

<b>methyl ethyl ketone (78-93-3)</b>	
Log Pow	0.3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 40 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.

# DURATEC THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>n-butyl acetate (123-86-4)</b>	
BCF fish 1	14 (Pisces)
Log Pow	1.79 - 2.06
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.

<b>isobutyl acetate (110-19-0)</b>	
BCF fish 1	4 - 9.7 (Pisces; Estimated value)
Log Pow	1.59 - 1.78
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.

<b>2-propanol (67-63-0)</b>	
Log Pow	0.05 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.

<b>Solvent Naptha Petroleum Aliphatic (Proprietary)</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

<b>methyl ethyl ketone (78-93-3)</b>	
Surface tension	0.024 N/m (20 °C)
Ecology - soil	Slightly harmful to plants.

<b>n-butyl acetate (123-86-4)</b>	
Surface tension	0.0145 N/m (25 °C)

<b>isobutyl acetate (110-19-0)</b>	
Surface tension	0.024 N/m (20 °C)

<b>2-propanol (67-63-0)</b>	
Surface tension	0.021 N/m (25 °C)

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to ...

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: Transport information

In accordance with DOT

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : PAINT RELATED MATERIAL

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

### Additional information

Other information : No supplementary information available.

### ADR

Transport document description : UN 1263, 3, II, (D/E)

Packing group (ADR) : II



# DURATEC THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 30  
Classification code (ADR) : F1  
Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :

Tunnel restriction code : D/E  
LQ : 5l  
Excepted quantities (ADR) : E2

### Transport by sea

UN-No. (IMDG) : 1263  
Proper Shipping Name (IMDG) : PAINT RELATED MATERIAL  
Class (IMDG) : 3 - Flammable liquids  
Packing group (IMDG) : II - substances presenting medium danger

### Air transport

UN-No. (IATA) : 1263  
Proper Shipping Name (IATA) : PAINT RELATED MATERIAL  
Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : II - Medium Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

methyl ethyl ketone (78-93-3)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
n-butyl acetate (123-86-4)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225

Eye Irrit. 2 H319

STOT SE 3 H336

Full text of H-phrases: see section 16

# DURATEC THINNER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11  
Xi; R36  
R66  
R67

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

No additional information available

#### 15.3. US State regulations

No additional information available

## SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. Not classified (Oral)	Acute toxicity (oral) Not classified
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Muta. 1B	Germ cell mutagenicity Category 1B
Skin Irrit. Not classified	Skin corrosion/irritation Not classified
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

: 2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive mixtures with water.



### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 1 Slight Hazard

Personal Protection : H

SDS US (GHS HazCom 2012)

To the best of our knowledge this SDS is accurate. To the extent allowed by law, this statement is made in lieu of any other warranties, expressed or implied including but not limited to any implied warranty of merchantability or fitness for a particular purpose and is in lieu of any other obligations or liability on the part of Dura Technologies, Inc.