

ASHLAND®		Page: 1
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Maxguard™ WG-LEI-5555 WHITE
GELCOAT
™ Trademark, Ashland or its subsidiaries, registered in
various countries

Recommended use of the chemical and restrictions on use

Use of the Substance/Mixture : Industrial chemical

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America EHS Customer Requests@ashland.com	Emergency telephone number 1-800-ASHLAND (1-800-274-5263) Regulatory Information Number 1-800-325-3751 Product Information 614-790-3333
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Combustible Dust :

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

Specific target organ systemic toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ systemic toxicity - repeated exposure (Inhalation) : Category 1 (Auditory system)

GHS Label element

ASHLAND		Page: 2
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

Hazard pictograms :



Signal Word :

Danger

Hazard Statements :

Flammable liquid and vapor.
May form combustible dust concentrations in air.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
Causes damage to organs (Auditory system) through prolonged or repeated exposure if inhaled.

Precautionary Statements :

Prevention:
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/ eye protection/ face protection.

Response:
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Get medical advice/ attention if you feel unwell.
If skin irritation or rash occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:
Dispose of contents/ container to an approved waste disposal plant.

ASHLAND®		Page: 3
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

Other hazards

Static Accumulating liquid

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Static Accumulator
 Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
STYRENE	100-42-5	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335 STOT RE 1; H372 Asp. Tox. 1; H304	25.30
TITANIUM DIOXIDE (TiO2)	13463-67-7	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	17.46
TALC	14807-96-6	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	6.00
ALUMINUM HYDROXIDE	21645-51-2	Not a hazardous substance or mixture.	5.08

SAFETY DATA SHEET

Revision Date: 05/09/2015

Print Date: 10/21/2015

SDS Number: 000000039682

Version: 1.0

Maxguard™ WG-LEI-5555 WHITE GELCOAT
 ™ Trademark, Ashland or its subsidiaries, registered
 in various countries
 591162

METHYLMETHACRYLATE	80-62-6	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1B; H317 STOT SE 3; H335	3.00
SILICA AMORPHOUS (SIO2)	7631-86-9	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	2.40
SILICA COLLOIDAL AMORPHOUS	112945-52-5		1.50

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
- If inhaled : Move to fresh air.
 IF INHALED: Call a POISON CENTER or doctor/ physician if you feel unwell.
 Keep patient warm and at rest.
 If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
 If on skin, rinse well with water.
 Wash contaminated clothing before re-use.
 If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.

ASHLAND		Page: 5
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Cough
effects on memory
loss of appetite
Shortness of breath
confusion
pain in the hands and feet
Difficulty in breathing
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
Causes damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Do not allow run-off from fire fighting to enter drains or water courses.
Organic dusts at sufficient concentration can form explosive mixtures in air.
- Hazardous combustion products : Hydrocarbons
carbon dioxide and carbon monoxide

ASHLAND		Page: 6
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

aluminum oxides
toxic fumes

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

Polymerization will take place under fire conditions. If polymerization occurs in a closed container, there is a possibility it will rupture violently. Cool storage container with water, if exposed to fire.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Use personal protective equipment.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Other information : Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.

ASHLAND®		Page: 7
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Take precautionary measures against static discharges.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Secondary operations, such as grinding and sanding, may produce dust.
Maintain good housekeeping. Do not permit dust layers to accumulate, for example, on floors, ledges, and equipment, in order to avoid any potential for dust explosion hazards.

For further guidance on prevention of dust explosions, refer to National Fire Protection Association (NFPA) 654: "Standard for the Prevention of Fire and Dust Explosions, from the Manufacturing, Processing and Handling of Combustible Particulate Solids".

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
STYRENE	100-42-5	TWA	20 ppm	ACGIH
		STEL	40 ppm	ACGIH
		REL	50 ppm 215 mg/m3	NIOSH/GUID E
		STEL	100 ppm	NIOSH/GUID

SAFETY DATA SHEET

Revision Date: 05/09/2015

Print Date: 10/21/2015

SDS Number: 000000039682

Version: 1.0

Maxguard™ WG-LEI-5555 WHITE GELCOAT
 ™ Trademark, Ashland or its subsidiaries, registered
 in various countries
 591162

			425 mg/m3	E
		TWA	100 ppm	OSHA/Z2
		Ceiling	200 ppm	OSHA/Z2
		MAX. CONC	600 ppm	OSHA/Z2
TITANIUM DIOXIDE (TiO2)	13463-67-7	TWA	10 mg/m3	ACGIH
		PEL	15 mg/m3 Total dust.	OSHA_TRANS
		TWA	1 mg/m3 Respirable fraction.	ACGIHLIS_P
TALC	14807-96-6	TWA	2 mg/m3 Respirable fraction.	ACGIH
		REL	2 mg/m3 Respirable.	NIOSH/GUIDE
		TWA	0.1 mg/m3 Respirable.	Z3
		TWA	0.3 mg/m3 Total dust.	Z3
ALUMINUM HYDROXIDE	21645-51-2	TWA	1 mg/m3 Respirable fraction.	ACGIH
METHYLMETHACRYLATE	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		REL	100 ppm 410 mg/m3	NIOSH/GUIDE
		PEL	100 ppm 410 mg/m3	OSHA_TRANS
		TWA	50 ppm	ACGIHLIS_P
		STEL	100 ppm	ACGIHLIS_P
SILICA AMORPHOUS (SiO2)	7631-86-9	REL	6 mg/m3	NIOSH/GUIDE
		TWA	0.8 mg/m3	Z3
		TWA	6 mg/m3	TN OEL
SILICA COLLOIDAL AMORPHOUS	112945-52-5	REL	6 mg/m3	NIOSH/GUIDE
		TWA	0.8 mg/m3	Z3

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
STYRENE	100-42-5	styrene	Venous blood	Sampling time: End of shift.	0.2 mg/l	
Remarks:	Semi-quantitative					
		Mandelic acid plus phenylglyoxylic acid	Creatinine in urine	Sampling time: End of shift.	400 mg/g	

ASHLAND		Page: 9
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

Remarks:	Nonspecific
----------	-------------

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.
Provide appropriate exhaust ventilation at places where dust is formed.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : Wear as appropriate:
impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid
Odour : No data available
Odour Threshold : No data available

ASHLAND®		Page: 10
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 212.9 °F / 100.5 °C
(1,013.25 hPa)
Calculated Phase Transition Liquid/Gas

Flash point : 79.0 °F / 26.1 °C
Method: Seta closed cup

Evaporation rate : No data available

Flammability (solid, gas) :

May form combustible dust concentrations in air (during processing).

Flammability (liquids) : Static Accumulating liquid

Flammability (liquids)
Upper explosion limit : Upper flammability limit
12.5 %(V)
Method: Calculated Explosive Limit

Lower explosion limit : lower flammability limit
1.1 %(V)
Method: Calculated Explosive Limit

Vapour pressure : 37.2 hPa (20 °C)
Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 1.078 g/cm³ (25 °C)

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm²/s (40 °C)

ASHLAND		Page: 11
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Hazardous polymerisation may occur.
Vapours may form explosive mixture with air.
This product does not present a dust explosion hazard as delivered. However, fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source, is a potential dust explosion hazard.

Conditions to avoid : Heat, flames and sparks.

Exposure to air.
Exposure to sunlight.
Exposure to moisture

Incompatible materials : Acids
aluminum
aluminum chloride
Amines
Bases
Copper
Copper alloys
fluorides
halogens
iron chloride
metal salts
nitrates
reducing agents
strong bases
Strong oxidizing agents
UV light.
Peroxides

Hazardous decomposition products : aluminum oxides
carbon dioxide and carbon monoxide
Hydrocarbons
toxic fumes

SECTION 11. TOXICOLOGICAL INFORMATION

ASHLAND		Page: 12
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

STYRENE:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 11.8 mg/l, 2770 ppm
Exposure time: 4 h
Test atmosphere: vapour

No observed adverse effect level (Humans): 100 ppm
Exposure time: 7 h
Test atmosphere: vapour

Acute dermal toxicity : LD 50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

TITANIUM DIOXIDE (TiO₂):

Acute oral toxicity : LD 50 (Rat): > 24,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): > 6,820 mg/m³
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD 50 (Rabbit): > 10,000 mg/kg

ALUMINUM HYDROXIDE:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 423
GLP: yes
Assessment: No adverse effect has been observed in acute oral toxicity tests.

METHYLMETHACRYLATE:

Acute oral toxicity : LD 50 (Rat): 7,800 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 29.8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg

SILICA AMORPHOUS (SiO₂):

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

ASHLAND®		Page: 13
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC 50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: No adverse effect has been observed in acute
inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg

SILICA COLLOIDAL AMORPHOUS:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal
absorption under GHS.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis., Individuals with direct skin contact with methyl methacrylate have experienced temporary loss of feeling and mild nerve damage in the fingers.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

STYRENE:

Species: Rabbit

Result: Irritating to skin

TITANIUM DIOXIDE (TiO₂):

Result: Possibly irritating to skin

TALC:

Result: Possibly irritating to skin

ALUMINUM HYDROXIDE:

Result: Not irritating to skin

Species: Rabbit

Method: OECD Test Guideline 404

Result: Not irritating to skin

GLP: yes

METHYLMETHACRYLATE:

Result: Irritating to skin

SILICA AMORPHOUS (SiO₂):

ASHLAND®		Page: 14
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

Result: Possibly irritating to skin

SILICA COLLOIDAL AMORPHOUS:

Result: Not irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

STYRENE:

Result: Irritating to eyes

Remarks: Vapour during processing may be irritating to the respiratory tract and to the eyes.

TITANIUM DIOXIDE (TiO₂):

Result: Possibly irritating to eyes

TALC:

Result: Possibly irritating to eyes

ALUMINUM HYDROXIDE:

Result: Possibly irritating to eyes

Remarks: Aluminum powder, uncoated

Species: Rabbit

Result: Not irritating to eyes

Method: OECD Test Guideline 405

GLP: yes

METHYLMETHACRYLATE:

Result: Slightly irritating to eyes

SILICA AMORPHOUS (SiO₂):

Result: Possibly irritating to eyes

SILICA COLLOIDAL AMORPHOUS:

Result: Not irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

STYRENE:

Exposure routes: Skin contact

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Result: negative

Exposure routes: inhalation (vapour)

Species: Humans

Assessment: Does not cause respiratory sensitisation.

ASHLAND®		Page: 15
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

Result: negative

ALUMINUM HYDROXIDE:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Did not cause sensitisation on laboratory animals.

GLP: yes

METHYLMETHACRYLATE:

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment : Styrene has been tested for carcinogenicity in rats and mice. Styrene caused lung tumors in mice only. These tumors are not considered to be relevant to humans.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

Components:

STYRENE:

Assessment: May cause respiratory irritation.

METHYLMETHACRYLATE:

Target Organs: Upper respiratory tract

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Causes damage to organs (Auditory system) through prolonged or repeated exposure if inhaled.

Components:

STYRENE:

Exposure routes: inhalation (vapour)

Target Organs: Auditory system

Assessment: Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

STYRENE:

Species: Human

85 mg/m³

Application Route: inhalation (vapour)

Species: Human

615 mg/kg

ASHLAND®	Page: 16
SAFETY DATA SHEET	Revision Date: 05/09/2015
	Print Date: 10/21/2015
	SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162	Version: 1.0

Application Route: Skin contact

Aspiration toxicity

Not classified based on available information.

Components:

STYRENE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Solvents may degrease the skin.

Components:

TITANIUM DIOXIDE (TiO₂):

Remarks: Lung

Carcinogenicity:

IARC

Group 2B: Possibly carcinogenic to humans

STYRENE 100-42-5

TITANIUM DIOXIDE (TiO₂) 13463-67-7

TALC 14807-96-6

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

Reasonably anticipated to be a human carcinogen

STYRENE 100-42-5

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

STYRENE:

Toxicity to fish : LC 50 (Pimephales promelas (fathead minnow)): 4.02 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): 4.7 mg/l
Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 4.9 mg/l
Exposure time: 72 h

Toxicity to daphnia and other : NOEC (Water flea (Daphnia magna)): 1.01 mg/l

ASHLAND®		Page: 17
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

aquatic invertebrates
(Chronic toxicity) Exposure time: 21 d

Toxicity to bacteria : EC 50 (activated sludge): ca. 500 mg/l
Exposure time: 0.5 h

Toxicity to soil dwelling organisms : NOEC (Eisenia fetida (earthworms)): 34 mg/kg
Exposure time: 14 d
Method: OECD Test Guideline 207

TITANIUM DIOXIDE (TiO₂):

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): > 1,000 mg/l
Exposure time: 48 h
Test Type: static test

METHYLMETHACRYLATE:

Toxicity to fish : LC 50 (Fathead minnow (Pimephales promelas)): 130 mg/l
Exposure time: 96 h
Method: Static

LC 50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): 69 mg/l
Exposure time: 48 h
Test Type: flow-through test

Toxicity to algae : EC 50 (Pseudokirchneriella subcapitata (algae)): > 110 mg/l
Exposure time: 72 h
Test Type: static test

Toxicity to fish (Chronic toxicity) : LC 50 (Danio rerio (zebra fish)): 33.7 mg/l
Exposure time: 35 d
Test Type: flow-through test
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Water flea (Daphnia magna)): 37 mg/l
Exposure time: 21 d
Test Type: flow-through test
Method: OECD Test Guideline 211

SILICA AMORPHOUS (SiO₂):

Toxicity to fish : LC 50 (Danio rerio (zebra fish)): > 10,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

SILICA COLLOIDAL AMORPHOUS:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

ASHLAND®		Page: 18
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

Persistence and degradability

Components:

STYRENE:

Biodegradability : Result: Readily biodegradable
Biodegradation: > 60 %
Exposure time: 10 d

METHYLMETHACRYLATE:

Biodegradability : Result: Readily biodegradable
Biodegradation: 94.3 %
Exposure time: 14 d
Method: OECD Test Guideline 301C

SILICA COLLOIDAL AMORPHOUS:

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

Bioaccumulative potential

Components:

STYRENE:

Bioaccumulation : Bioconcentration factor (BCF): < 100

Partition coefficient: n-octanol/water : log Pow: 2.96 (25 °C)

METHYLMETHACRYLATE:

Partition coefficient: n-octanol/water : log Pow: 1.38

Mobility in soil

Components:

STYRENE:

Distribution among environmental compartments : Koc: 352

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

Components:

STYRENE:

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

SAFETY DATA SHEET

Revision Date: 05/09/2015

Print Date: 10/21/2015

SDS Number: 000000039682

Version: 1.0

Maxguard™ WG-LEI-5555 WHITE GELCOAT
 ™ Trademark, Ashland or its subsidiaries, registered
 in various countries
 591162

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

SECTION 14. TRANSPORT INFORMATION**International transport regulations****REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

UN 1866	Resin solution	3		III	
---------	----------------	---	--	-----	--

U.S. DOT - RAIL

UN 1866	Resin solution	3		III	
---------	----------------	---	--	-----	--

U.S. DOT - INLAND WATERWAYS

UN 1866	Resin solution	3		III	
---------	----------------	---	--	-----	--

TRANSPORT CANADA - ROAD

UN 1866	RESIN SOLUTION	3		III	
---------	----------------	---	--	-----	--

TRANSPORT CANADA - RAIL

UN 1866	RESIN SOLUTION	3		III	
---------	----------------	---	--	-----	--

TRANSPORT CANADA - INLAND WATERWAYS

UN 1866	RESIN SOLUTION	3		III	
---------	----------------	---	--	-----	--

INTERNATIONAL MARITIME DANGEROUS GOODS

UN 1866	RESIN SOLUTION	3		III	
---------	----------------	---	--	-----	--

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN 1866	Resin solution	3		III	
---------	----------------	---	--	-----	--

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

ASHLAND®		Page: 20
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

UN	1866	Resin solution	3	III
----	------	----------------	---	-----

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1866	RESINA, SOLUCIONES DE	3	III
----	------	-----------------------	---	-----

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	yes
------------------	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
STYRENE	100-42-5	1000	3952.491057

SARA 311/312 Hazards : Reactivity Hazard
Acute Health Hazard
Fire Hazard
Chronic Health Hazard

SARA 313 Component(s)

STYRENE	100-42-5	25.30 %
METHYLMETHACRYLATE	80-62-6	3.00 %
COBALT 2-ETHYLHEXANOATE	136-52-7	0.09 %
COBALT NEODECANOATE	27253-31-2	0.02 %
COBALT HYDROXIDE	21041-93-0	0.00 %

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.
1,3, BUTADIENE 106-99-0

ASHLAND®	Page: 21
SAFETY DATA SHEET	Revision Date: 05/09/2015
	Print Date: 10/21/2015
	SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162	Version: 1.0

LEAD	7439-92-1
ETHYLENE OXIDE	75-21-8
ACETALDEHYDE	75-07-0
1,4-DIOXANE	123-91-1
FORMALDEHYDE	50-00-0
BENZENE	71-43-2
QUARTZ / SAND	14808-60-7
ETHYL BENZENE	100-41-4
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
BENZENE	71-43-2
ETHYLENE OXIDE	75-21-8
ETHYLENE GLYCOL MONOMETHYL ETHER	109-86-4
TOLUENE	108-88-3
LEAD	7439-92-1
1,3, BUTADIENE	106-99-0
METHYL CHLORIDE	74-87-3

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AUSTR : Not in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECL : Not in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories

ASHLAND®		Page: 22
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/09/2015

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td>HEALTH</td> <td>2*</td> </tr> <tr> <td>FLAMMABILITY</td> <td>3</td> </tr> <tr> <td>PHYSICAL HAZARD</td> <td>2</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2*	FLAMMABILITY	3	PHYSICAL HAZARD	2
HEALTH	2*						
FLAMMABILITY	3						
PHYSICAL HAZARD	2						

NFPA Flammable and Combustible Liquids Classification

Flammable Liquid Class IC

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.

Sources of key data used to compile the Safety Data Sheet

Ashland internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the

ASHLAND®		Page: 23
SAFETY DATA SHEET		Revision Date: 05/09/2015
		Print Date: 10/21/2015
		SDS Number: 000000039682
Maxguard™ WG-LEI-5555 WHITE GELCOAT ™ Trademark, Ashland or its subsidiaries, registered in various countries 591162		Version: 1.0

information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System